

Category 6A Field Termination Plug

molex

The Molex Category 6A field termination plug is designed to support 10gb networks and can be easily terminated using parallel jaw pliers.

Termination is accomplished by placing the conductors into the proper wire slots in the wire cap. Placing the wire cap onto the plug, using a pliers to squeeze the wiring cap. All eight conductors are simultaneously terminated when the wire cap is squeezed. This process ensures quick, consistent, reliable terminations. The IDC is designed to accommodate different diameter conductors from 22 AWG-26 AWG Solid Wire. The Field Terminable Plug meets TIA-568.2-D Category 6A component performance, Cat 5e/6 and 6A Direct Attach link and channels.

Ideal for use to provide high-bandwidth wireless access points and other IP-enabled devices such as: Surveillance cameras and infrastructure monitoring. A field modular plug that is simple to terminate and meets Cat 6A performance requirements is also ideal in data centres, premise network applications, premise automation such as lighting, HVAC and other environmental sensor applications.



Features and Advantages

Supports 10gb networks

Designed to accommodate conductors from 22 AWG - 26 AWG

TIA-568.2-D Category 6A component performance

UL listed

Ideal for wireless access points and IP-enabled devices, data centres and premise network applications

www.molexces.com

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners. This information is correct at the time of publication, specifications are subject to change.

Order No. KSP-00001

USA/0k/RJ/2020.01

©2020 Molex

Category 6A Field Termination Plug



Specifications

COMMERCIAL STANDARDS

IEC 60603-7-5
UL Listed

MECHANICAL

Transmission performance: Cat.6A/Class EA Direct
attach link and channels
Plug protection category: IP 20
Wiring label: TIA 568A/B & PNO
Termination capability:
Solid wire: 22-26 AWG
Stranded wire: 22-27 AWG
Re-termination capability: 5 times
Supporting cable diameter: 6-9mm
Plug Housing: Zinc Alloy
Plug Pins: Phosphor bronze with 50u"
gold plating
Durability: 750 mechanical cycles

ELECTRICAL

Current rating: 1.5A
Dielectric withstanding voltage: 1000V DC
Insulation resistance: 500M Ω min.
Contact resistance: 20m Ω max

Ordering Information

Order No.	SAP No.	Description
KSP-00001	18301-0086	Category 6A Field Termination Plug

www.molexces.com

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners. This information is correct at the time of publication, specifications are subject to change.